



ZYTRONIC DATA SHEET

ZyBrid®

ZyBrid® touch sensors are based on our award winning and durable Projected Capacitive Technology (PCT™) and are available in a limitless range of customisable designs



ADVANTAGES

- Highly durable, vandal and scratch resistant
- Fast and accurate response times
- Performance unaffected by moisture and surface contaminants.
- Operation with gloved and un-gloved finger.
- Drift-free operation - no recalibration required.

FEATURES

- Chemically, physically and mechanically inert glass touch surface
- Ability to create a fully sealed design that complies with NEMA a, 12 and IP 65 standards
- Size range from 5" - 85"
- Single and Dual touch performance when coupled with a ZXY100™ or ZXY110™ controller
- Excellent light transmission with optional optical coating enhancements
- Compatible with a variety of operating systems including Linux
- Customisable options including, glass thickness and surface treatment, printed borders and customer logo's.

OPERATION

The screen is divided into a X - Y matrix of sensing cells of embedded 10µm copper electrodes which are near invisible to the human eye on a powered display. These electrodes are connected to an electronic controller board, and an oscillation frequency is established for each track.

When a finger or conductive stylus approaches the surface of the sensor, a change in the oscillating frequency of the tracks around that particular point is registered; the position is then determined by the controller and firmware combination. Unlike conventional capacitive systems the active component of PCT™ is embedded behind the front substrate, ensuring protection, long life, and stability.

The unique sensing characteristics of PCT™ sensing eliminates the need for an operating force. Furthermore the sensors are unaffected by rain, dirt and scratches.

APPLICATIONS

Zytron's **ZyBrid®** touch sensors are a durable and cost effective method to meet today's demanding touch screen requirements. The construction is resistant to damage caused by moisture, heat and surface contaminants making **ZyBrid®** the perfect choice for signage, leisure, retail applications whether indoors or outdoors.

INNOVATIONS

Normal **ZyBrid®** touch sensors are capable of detecting 1 or 2 touches. Our latest Multi Touch **ZyBrid®** sensors capable of detecting up to 40 independent touches, whilst still offering the same durable performance. For more information see Multi Touch **ZyBrid®** data sheet.

ZyBrid® SPECIFICATION



SENSOR

Detection Method	Projected Capacitive Technology (PCT™) self capacitive type
Sensor	Glass with embedded micro-fine sensing array
Control electronics	Remotely sited PCB, Serial or USB connectivity
Size range	5" - 85"
Optical Resolution	>4 lines/mm (NBS1963A)
Light Transmission	~90%
Haze	<3% (Gardner Haze) If Anti glare glass specified

CONTROLLER

See data sheet for ZXY100° and ZXY110° touch controller

MECHANICAL

Immunity to damage	Glass surface with no moving parts
Sensor thickness	1 - 10mm
Stylus type	Finger, gloved hand and conductive stylus
Operation Force	<0.1g
Hardness	Glass hardness – Mohs 7
Sensor MTBF	Glass with no moving parts or coatings. No known wear out mechanisms
Sealing	Can be sealed to meet NEMA 4, 12 and IP 65 standards
Vibration	In accordance with IEC 60068-2-64 when installed in a suitable bezel
Options	Various glass types and thickness's available; custom screen printed borders/logos; flat or curved glass; drill holes, slots and edge profiles.

ENVIRONMENT

Operating Temperature	-35°C to +70°C
Humidity	RH 0-90% up to 40°C
Storage Temperature	-40°C to 80°C
Storage Humidity	RH 0-90% up to 40°C
Resistance to Contamination	Sensing media protected by glass, exceeds requirements of ASTM-F1598-96
Water Resistance	Unaffected by water droplets or condensation

QUALITY

See cosmetic specification	www.zytronic.co.uk
----------------------------	--

APPROVALS

RoHS compliant	
CE, FCC & UL approved	www.zytronic.co.uk

ZyBrid®, ZYTRONIC and its logo are registered in the United Kingdom and other countries.



Company No: 379908. Registered in England. VAT No: GB 746 4858 88

Whiteley Road
Blaydon on Tyne
Tyne & Wear
NE21 5NJ
United Kingdom

T: +44 (0) 191 414 5511
F: +44 (0) 191 414 0545
E: info@zytronic.co.uk

www.zytronic.co.uk